WalT: A Reproducible Research Platform for Networks and Distributed Data

Etienne Dublé (LIG / CNRS), Franck Rousseau (LIG / Grenoble INP) and Drakkar team of LIG lab Grenoble, September 2020



This is a typical wireless network experiment! ;)

Motivation

Sample use case

Architecture

WalT under the hood

News, On-going work and Perspectives

Large scale testbeds (e.g. IoT-Lab)

- Limited hardware choice
- Static environment & network topology
- No physical access (for debugging)
- Booking system sometimes crowded

Handmade platform "on your own desk"

- Does not scale
- Is hardly reproducible





WalT stands halfway between those 2 categories.

Just as a handmade platform,

- WaIT can be lightweight (backpack-compatible, for a demo)
- You can build several instances of WalT
- You can set up one on your desk (for debugging)
- You can easily move nodes (CPS, wireless networks)

Just as a large-scale platform,

- You can make it bigger (you can deploy it in a building)
- It is easy to use

We provide:

- Open source code
- Installation images
- Documentation (how to install and use)
- Support (walt-users@univ-grenoble-alpes.fr)

We do not provide:

• A publicly available platform (you should build your own)

Motivation


Sample use case


Architecture


WalT under the hood


News, On-going work and Perspectives














































































































































Motivation

Sample use case

Architecture

WalT under the hood

News, On-going work and Perspectives

What is a WalT node?



- Historically, a WalT node was a Single-Board-Computer¹ preferably powered through PoE
- Its OS is a "WalT image" shared from the server through TFTP/NFS

2 cases:

- 1. WalT nodes run the experiment, or
- WalT nodes control the target devices of the experiment (e.g., ST sensor board in the picture)

¹We support Raspberry Pi B/B+/2B/3B/3B+/4B and x86 boards.

WalT now supports other kinds of nodes:

- Any PC can become a WalT node, by booting a USB stick flashed appropriately
- One can also create virtual nodes (kvm)

Network isolation

- WalT wired network is isolated from internet by default.
 (→ improve reproducibility)
- If it's needed, walt node netsetup command can still toggle NAT mode on a node, to allow internet access.

VPN and distant nodes


- WALT version 5 now has experimental support for distant nodes (cf. LoRa, SigFox).
- These nodes reach WalT network through a VPN (+ a level of virtualization to implement network boot procedure)

WalT is a reproducible platform¹

- Any researcher can build its own WalT platform
- ... or several platforms of various scales (e.g., one for debugging, one for experiments)

¹P. Brunisholz, E. Duble, F. Rousseau, and A. Duda, "WalT: A Reproducible Testbed for Reproducible Network Experiments", in Proc. of the International Workshop on Computer and Networking Experimental Research Using Testbeds, 2016.

Sample mobile setup




Minimal setup for an ANR Datatweet meeting

WalT versatility shown in two slides (1)




A node of the WalT network in IMAG building

WalT versatility shown in two slides (2)




Reusing the same wall plug for temporary low-level debugging

Architecture for WSNs



In this case:

- We want to monitor *sensor nodes*
- WalT nodes are "controller nodes" (e.g., flash sensor nodes, save logs, debug using the serial link)
- A WalT image provides this support



- A Cooja simulator plugin
- It makes *Cooja* show the behavior of real sensor nodes (instead of simulating)
- Input: logs coming from sensor nodes
- VizWalT visualizes what's happening in the network, in real time or post mortem

Motivation


Sample use case

Architecture

WalT under the hood

News, On-going work and Perspectives


Node boot procedure



- NFS: Network File System
- Allows to expose locally a view of the files stored elsewhere
- Each access to a file is translated into a request-response to NFS server
- Comparison:

Local file system: requests go to disk controller Network file system: requests go to remote server

• Consequence: WalT images stay on the server. A WalT image is never transfered as a whole to the node.



Benefits of this boot procedure:

- WalT images embed a kernel, an OS filesystem, bootloader scripts: the whole software stack can be customized.
- The SD card of a node just contains a network bootloader:
 => It remains read-only (this ensures robustness over time)
- Nodes are completely stateless:
 - At each reboot, they just download /start.uboot and run it (the server maintains redirections to the selected walt image)
 - File modifications (stored in RAM) are lost on reboot: when booting the same image, OS restarts exactly the same (this ensures **reproducibility**)

Other technical highlights:

- "walt image shell" command:
 - Provides a shell session rooted inside the image
 - Allows to modify an existing image very easily
 - Behind the scenes, a *docker container* is created on server
 - Transparent cross-CPU-architecture is handled using qemu
- "walt node boot" command:
 - Exposes the content of a docker image as an NFS share
 - Lets the node(s) boot it
 - In short, this instantly turns a virtual image into a real deployment.

Motivation

Sample use case

Architecture

WalT under the hood

News, On-going work and Perspectives

Recent news

- WALT v5 is available since september 8, 2020
- Schneider Electric has built a demonstrator based on WalT (with our help)
- Other platforms have been setup (Lyon, Istanbul)
- WaIT is also used for wifi hands-on at Grenoble INP Ensimag
- The deployment in IMAG building at LIG now has 12 more 3B+ nodes on the ground floor
- We connected our WalT platform at IMAG to our data management platform (https://sakura-platform.liglab.fr/)

On-going or for the near future

- Design of a more efficient network filesystem (wrt. NFS) for high-latency networks (e.g. VPN)
- Several network experiments (Drakkar team at LIG)
- Possible network monitoring experiments in the IMAG building¹
- Possible new walt deployments (e.g. at LAAS (Toulouse), at Bu-Ali Sina University (Iran))
- Several planned software improvements²

¹with G. Enderlé, É. Jullien of Grenoble University ²https://github.com/drakkar-lig/walt-python-packages/issues

- get help:
 - register to the list: walt-users@univ-grenoble-alpes.fr
 - or checkout: https://walt-project.liglab.fr, section "Resources and Documentation"
 - or type: walt help show
- or just contact us:
 - email: walt-contact@univ-grenoble-alpes.fr

- Setup¹ and use your own platform, and
 - Share your WalT images on the *docker hub*
 - Add support for new kinds of nodes
 - Report bugs
- Discuss with us possible improvements

¹Contact us (walt-contact@univ-grenoble-alpes.fr), we will assist you.

WalT credits

- Initial funding
 - Univ. Grenoble Alpes, Grenoble INP / UJF, AGIR WalT (2013-2014)
 - ANR IRIS (2011)
 - FP7 ICT CALIPSO Connect All IP-based Smart Objects (2011)
 - ANR DataTweet (2013)
- Thanks
 - Pierre Brunisholz, Baptiste Jonglez, Narek Davtyan, Ayoub Bargach, Mehmet Tahir Sandikkaya, Qasim Lone, Takwa Attia, Rémy Grünblatt, Paul Grangette, WalT images design, development, testing & documentation
 - Bastien Faure, Pierre-Henry Frohring, Jorane Congio-Hollard, Cosmin Nichifor, core WalT
 - Jorge Luis Baranguan Castro, VizWalT
 - Henri-Joseph Audéoud, Elodie Morin, Timothy Claeys, Onss Bousbih, testing and demo setup
 - Joao Guilherme Zeni, Matheus Castanho, lacob Juc, Liviu Varga, sensor integration & Contiki instrumentation

Questions?